

FEATURES:

Slim wall socket housing

MTBF – 50 000 h

Meets energy star level V

Universal AC input / full range



SPECIFICATION:

output	Model	Voltage DC [V]	Current min [A]	Current max. [A]	Tolerance [%]	Efficiency [%]	Power max. [W]	Ripple & noise [mV]	DC plug & polarity
	ESPE 0909-0723	9	0	1	+/- 5	>73	9	120	0.7x2.35 center positive
input	voltage	100 - 240V							
	voltage range	90 - 264V							
	frequency min. / max	47 - 63 Hz							
	frequency	60HZ / 50Hz							
	current	0,3Amax@100VAC							
	inrush current	20Amax@240VAC							
protection	OCP	Overload							
	OVP	Over voltage							
	SC	Short circuit							
	insulation	Class II							
	min. load requirement	No							
others	MTBF	50000h							
	efficiency	> 73 %							
	dimensions / weight	70 x27 x 38 mm / 86 g (100pcs/cartoon)							
environmental	operating temp.	0 ~40 deg C							
	storage temp.	-10 ~80 deg C							
	relative humidity	25% ~75% RH							
	storage relative humidity	25% ~75% RH							
safety	CE	EN60950-1							
	TUV - GS	EN60950-1							
EMC	EMI	EN 55022:1998, +A1:2000 +A2:2003, CLASS B							