



# deSIGN 42 - pre-assembled Signal Tower

## Your benefits

Thanks to its high-quality stainless steel housing, the deSIGN 42 signal tower is an ideal accompaniment to modern, design-oriented assembly lines, production facilities and machinery. The robust housing provides the key benefit of being tamper-proof for installations in public areas.

- Elegant industrial design
- Tamper-proof for public areas

## Typical applications

Fault signalling

- on machinery and equipment

Access control

- on control points in public areas

## Installation options


- Single-hole mounting
- Bracket mounting using accessories

## Features

- High-quality, robust stainless-steel housing
- Award-winning design



Size comparison deSIGN 42 / KombiSIGN 72





### ❶ TECHNICAL SPECIFICATIONS/ORDER SPECIFICATIONS:

	2 tier	3 tier
Dimensions (Ø x Height):	42 mm x 221 mm	42 mm x 255 mm
Housing:	Stainless steel, brushed	
Fixing:	Installation mounting for Ø 22.5 mm (M22 x 1.5 mm)	
Connection:	Cable, 2 m long, included in assembly	
Voltage:	24 V DC	24 V DC
Current consumption:	50 mA per tier	50 mA per tier
red/green	<b>694 010 55</b>	-
red/yellow	<b>694 020 55</b>	-
red/yellow/green	-	<b>694 000 55</b>

### ✂ ACCESSORIES:

Surface housing single	<b>975 109 02</b>
Bracket, stainless steel (Protection rating IP 33)	<b>960 694 01</b>

### ↩ TECHNICAL DIAGRAMS:

