


### 2.0 Amp. Surface Mounted Glass Passivated Ultrafast Soft Recovery Rectifier

SOD128	Voltage	Current
	200 V	2.0 A
	<b>FEATURES</b> <ul style="list-style-type: none"> <li>• Top-Glass Technology</li> <li>• Low profile package</li> <li>• Ideal for automated placement</li> <li>• Low power losses, high efficiency</li> <li>• High surge current capability</li> <li>• Cavity-free glass passivated junction</li> <li>• Low forward voltage drop</li> <li>• Solder dip 260 °C, 10s</li> <li>• AEC-Q101 qualified</li> <li>• Component in accordance to RoHS 2011/65/EU and WEEE 2002/96/EC</li> <li>• Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C</li> <li>• Very soft recovery characteristics</li> <li>• Significantly reduced EMI. Very low Noise.</li> </ul>	
	<b>MECHANICAL DATA</b> <ul style="list-style-type: none"> <li>• <b>Case:</b> SOD128. Epoxy meets UL 94V-0 flammability rating.</li> <li>• <b>Polarity:</b> Color band denotes cathode end.</li> <li>• <b>Terminals:</b> Matte tin plated leads, solderable per MIL-STD-750 Method 2026, J-STD-002 and JESD22-B102. Consumer grade, meets JESD 201 class 1A whisker test.</li> <li>• <b>HE3 suffix</b> for high reliability grade, meets JESD 201 class 2 whisker test.</li> </ul>	
	<b>TYPICAL APPLICATIONS</b> Used in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer, automotive and telecommunication.	



**RoHS**  
COMPLIANT

### Maximum Ratings and Electrical Characteristics at 25 °C

		FES2DZSR
Marking Code		KB
$V_{RRM}$	Maximum Recurrent Peak Reverse Voltage (V)	200
$V_{RMS}$	Maximum RMS Voltage (V)	140
$V_{DC}$	Maximum DC Blocking Voltage (V)	200
$I_F (AV)$	Forward current at $T_L = 145\text{ °C}$	2.0 A
$C_j$	Typical Junction Capacitance (1MHz; -4V)	40 pF
$R_{th(j-a)}$	Maximum Thermal Resistance Junction to Ambient: • FR4 PCB Standard Footprint • FR4 PCB Mounting Pad for Cathode 1cm <sup>2</sup>	150 °C/W 94 °C/W
$R_{th(j-sp)}$	Maximum Thermal Resistance Junction to Solder Point	13 °C/W
$T_j - T_{stg}$	Operating Junction and Storage Temperature Range	- 65 to + 175 °C

Symbol	Parameter	Value	Units
$I_{FSM}$	Non Repetitive surge peak forward current (8.3 msg. peak forward surge JEDEC Method)	100A	Amps.

**2.0 Amp. Surface Mounted Glass Passivated Ultrafast Soft Recovery Rectifier**
**Static Electrical Characteristics**

Symbol	Parameter	Test Conditions	Max.	Unit
$V_F$	Max. Instantaneous Forward Voltage	$T_j = 25\text{ }^{\circ}\text{C}$ $I_F = 2.0\text{ A}$	0.90	V
		$T_j = 100\text{ }^{\circ}\text{C}$ $I_F = 2.0\text{ A}$	0.75	
		$T_j = 25\text{ }^{\circ}\text{C}$ $I_F = 0.7\text{ A}$	0.80	
$I_R$	Max. DC Reverse Leakage Current	$T_j = 25\text{ }^{\circ}\text{C}$ $V_R = V_{RR}$	5	$\mu\text{A}$
		$T_j = 100\text{ }^{\circ}\text{C}$ $V_R = V_{RR}$	10	
		$T_j = 175\text{ }^{\circ}\text{C}$ $V_R = V_{RR}$	100	

**Recovery Characteristics ( $T_j = 25\text{ }^{\circ}\text{C}$ )**


Symbol	Test Conditions	Min.	Max.	Typ.	Unit
$t_{rr}$	$I_F = 0.5\text{ A}$ , $dI_F/dt = 100\text{ A}/\mu\text{s}$ , $I_{rr} = 1000\text{ mA}$		25		ns
$t_a$				15	
$t_b$				6	
$t_b/t_a$	Softness	0.45			
$Q_{rr}$	$V_R = 30\text{V}$ , $dI_F/dt = 50\text{ A}/\mu\text{s}$ , $I_F = 1\text{A}$			15	nC
	$V_R = 30\text{V}$ , $dI_F/dt = 50\text{ A}/\mu\text{s}$ , $I_F = 2\text{A}$			20	
	$V_R = 30\text{V}$ , $dI_F/dt = 50\text{ A}/\mu\text{s}$ , $I_F = 5\text{A}$			25	
	$V_R = 30\text{V}$ , $dI_F/dt = 50\text{ A}/\mu\text{s}$ , $I_F = 20\text{A}$			60	

**2.0 Amp. Surface Mounted Glass Passivated Ultrafast Soft Recovery Rectifier**





**Ordering information**

PREFERRED P/N	PACKAGE CODE	DELIVERY MODE	BASE QUANTITY	UNIT WEIGHT (g)
FES2DZSR HE3 TRTB	TRTB	13" diameter tape and reel	10,000	0.0180

**Package Outline Dimensions: (mm) SOD128**



**2.0 Amp. Surface Mounted Glass Passivated Ultrafast Soft Recovery Rectifier**
**Ratings and Characteristics** (Ta 25°C unless otherwise noted)

**Fig. 1 REVERSE CURRENT vs REVERSE VOLTAGE**

**Fig. 2 FORWARD VOLTAGE vs FORWARD CURRENT**

**Fig. 3 LOW FREQUENCY POWER LOSSES vs. AVERAGE CURRENT**

**Fig. 4 PEAK CURRENT vs. FORM FACTOR**


## 2.0 Amp. Surface Mounted Glass Passivated Ultrafast Soft Recovery Rectifier

### Ratings and Characteristics (Ta 25°C unless otherwise noted)

Fig. 5 FORWARD CURRENT DERATING CURVE




Fig. 6  $t_b/t_a$  CURVES vs. FORWARD CURRENT




Fig. 7  $t_{rr}$ ,  $t_a$  AND  $t_b$  CURVES vs FORWARD CURRENT.  $T_C = 25°C$




Fig. 8  $t_{rr}$ ,  $t_a$  AND  $t_b$  CURVES vs FORWARD CURRENT.  $T_C = 100°C$




Fig. 9 RECOVERY TIME vs  $dI_F/dt$















Fig. 10 PEAK REVERSE CURRENT vs  $dI_F/dt$





**2.0 Amp. Surface Mounted Glass Passivated Ultrafast Soft Recovery Rectifier**
**Ratings and Characteristics** (Ta 25°C unless otherwise noted)

**Fig.11 trr vs  $di_F/dt$ .  $I_F = 2$  A**

**Fig.12 trr vs  $di_F/dt$ .  $I_F = 0.1$  A**

**Fig.13 trr vs  $di_F/dt$ .  $I_F = 0.5$  A**

**Fig.14 QRR vs JUNCTION TEMPERATURE**

**Fig.15 IRM vs JUNCTION TEMPERATURE**

**Fig.16 trr vs JUNCTION TEMPERATURE**


**2.0 Amp. Surface Mounted Glass Passivated Ultrafast Soft Recovery Rectifier**
**Ratings and Characteristics** ( $T_a$  25°C unless otherwise noted)

**Fig. 17 TRANSIENT PEAK FORWARD VOLTAGE vs  $di_F/dt$** 

**Fig. 18 FORWARD RECOVERY TIME vs  $di_F/dt$** 

**Fig. 19 RECOVERY TIME vs JUNCTION TEMPERATURE**

**Fig. 20 JUNCTION CAPACITANCE vs. REVERSE BIAS**


**2.0 Amp. Surface Mounted Glass Passivated Ultrafast Soft Recovery Rectifier**
**Ratings and Characteristics** ( $T_{amb} = 25^{\circ}\text{C}$  unless otherwise noted)

**Fig. 21 RELATIVE VARIATION OF THERMAL IMPEDANCE TO AMBIENT vs. PULSE DURATION**

**Fig. 22 RELATIVE VARIATION OF THERMAL IMPEDANCE TO AMBIENT vs. PULSE DURATION**




**2.0 Amp. Surface Mounted Glass Passivated Ultrafast Soft Recovery Rectifier****Revision History**

DATE	REVISION	DESCRIPTION OF CHANGES
20-Jun-2015	0	Original Data Sheet
25-Aug-2016	1	Marking Code Modified
16-Oct-2018	2	Include: Typical Transient Thermal Impedance

**Disclaimer**

All product, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.

Fagor Electrónica, S. Coop., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Fagor"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Fagor makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Fagor disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Fagor's knowledge of typical requirements that are often placed on Fagor products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Fagor's terms and conditions or purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Fagor products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Fagor product could result in personal injury or death. Customers using or selling Fagor products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Fagor and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Fagor or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Fagor personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Fagor. Products names and markings noted herein may be trademarks of their respective owners.