

### FEATURES

- Low input offset voltage 150  $\mu$ V max**
- Low offset voltage drift over  $-55^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ , 1.2  $\mu\text{V}/^{\circ}\text{C}$  max**
- Low supply current (per amplifier) 725  $\mu\text{A}$  max**
- High open-loop gain 5000 V/mV min**
- Input bias current 3 nA max**
- Low noise voltage density 11 nV/ $\sqrt{\text{Hz}}$  at 1 kHz**
- Stable with large capacitive loads 10 nF typ**
- Pin compatible to LM148, HA4741, RM4156, and LT1014 with improved performance**
- Available in die form**

### GENERAL DESCRIPTION

The OP400 is the first monolithic quad operational amplifier that features OP77-type performance. Precision performance is not sacrificed with the OP400 to obtain the space and cost savings offered by quad amplifiers.

The OP400 features an extremely low input offset voltage of less than 150  $\mu$ V with a drift of under 1.2  $\mu\text{V}/^{\circ}\text{C}$ , guaranteed over the full military temperature range. Open-loop gain of the OP400 is over 5,000,000 into a 10 k $\Omega$  load, input bias current is under 3 nA, CMR is above 120 dB, and PSRR is below 1.8  $\mu\text{V}/\text{V}$ . On-chip Zener zap trimming is used to achieve the low input offset voltage of the OP400 and eliminates the need for offset nulling. The OP400 conforms to the industry-standard quad pinout which does not have null terminals.

### FUNCTIONAL BLOCK DIAGRAM





Figure 1. 14-Pin Ceramic DIP (Y-Suffix)  
and 14-Pin Plastic DIP (P-Suffix)

Figure 2. 16-Pin SOIC (S-Suffix)

00304-001  
00304-002

The OP400 features low power consumption, drawing less than 725  $\mu\text{A}$  per amplifier. The total current drawn by this quad amplifier is less than that of a single OP07, yet the OP400 offers significant improvements over this industry-standard op amp. Voltage noise density of the OP400 is a low 11 nV/ $\sqrt{\text{Hz}}$  at 10 Hz, which is half that of most competitive devices.

The OP400 is pin compatible with the LM148, HA4741, RM4156, and LT1014 operational amplifiers and can be used to upgrade systems having these devices. The OP400 is an ideal choice for applications requiring multiple precision operational amplifiers and where low power consumption is critical.



00304-003

Figure 3. Simplified Schematic (One of Four Amplifiers Is Shown)

Rev. D

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

## TABLE OF CONTENTS

Features .....	1	Typical Performance Characteristics .....	7
Functional Block Diagram .....	1	Applications.....	12
General Description .....	1	Dual Low Power Instrumentation Amplifier .....	12
Revision History .....	2	Bipolar Current Transmitter.....	13
Specifications.....	3	Differential Output Instrumentation Amplifier .....	13
Electrical Characteristics.....	3	Multiple Output Tracking Voltage Reference.....	14
Absolute Maximum Ratings.....	6	Outline Dimensions .....	15
Thermal Resistance .....	6	Ordering Guide .....	16
ESD Caution.....	6	SMD Parts and Equivalents .....	16

## REVISION HISTORY

### 3/06—Rev. C to Rev. D.

Updated Format .....	Universal
Deleted Wafer Test Limits Table .....	4
New Package Drawing: R-14 .....	15
Updated Outline Dimensions .....	15
Changes to Ordering Guide .....	16

### 6/03—Rev. B to Rev. C.

Edits to Specifications .....	2
-------------------------------	---

### 10/02—Rev. A to Rev. B.

Addition of Absolute Maximum Ratings .....	5
Edits to Outline Dimensions.....	12

### 4/02—Rev. 0 to Rev. A.

Edits to Features.....	1
Edits to Ordering Information.....	1
Edits to Pin Connections.....	1
Edits to General Descriptions .....	1, 2
Edits to Package Type.....	2

# SPECIFICATIONS

## ELECTRICAL CHARACTERISTICS

@  $V_S = \pm 15$  V,  $T_A = +25^\circ\text{C}$ , unless otherwise noted.

Table 1.

Parameter	Symbol	Conditions	OP400A/E			OP400F			OP400G/H			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
<b>INPUT CHARACTERISTICS</b>												
Input Offset Voltage	$V_{OS}$			40	150		60	230		80	300	$\mu\text{V}$
Long-Term Input Voltage Stability				0.1			0.1			0.1		$\mu\text{V}/\text{mo}$
Input Offset Current	$I_{OS}$	$V_{CM} = 0^\circ\text{V}$		0.1	1.0		0.1	2.0		0.1	3.5	nA
Input Bias Current	$I_B$	$V_{CM} = 0^\circ\text{V}$		0.75	3.0		0.75	6.0		0.75	7.0	nA
Input Noise Voltage	$e_{n,p-p}$	0.1 Hz to 10 Hz		0.5			0.5			0.5		$\mu\text{V p-p}$
Input Resistance Differential Mode	$R_{IN}$			10			10			10		$M\Omega$
Input Resistance Common Mode	$R_{INCM}$			200			200			200		$G\Omega$
Large Signal Voltage Gain	$A_{VO}$	$V_O = \pm 10$ V $R_L = 10$ k $\Omega$	5000	12,000		3000	7000		3000	7000		$\text{V}/\text{mV}$
		$R_L = 2$ k $\Omega$	2000	3500		1500	3000		1500	3000		$\text{V}/\text{mV}$
Input Voltage Range <sup>1</sup>	IVR		$\pm 12$	$\pm 13$		$\pm 12$	$\pm 13$		$\pm 12$	$\pm 13$		V
Common-Mode Rejection	CMR	$V_{CM} = 12$ V	120	140		115	140		110	135		dB
Input Capacitance	$C_{IN}$			3.2			3.2			3.2		pF
<b>OUTPUT CHARACTERISTICS</b>												
Output Voltage Swing	$V_O$	$R_L = 10$ k $\Omega$	$\pm 12$	$\pm 12.$ 6		$\pm 12$	$\pm 12.$ 6		$\pm 12$	$\pm 12.$ 6		V
<b>POWER SUPPLY</b>												
Power Supply Rejection Ratio	PSRR	$V_S = 3$ V to 18 V		0.1	1.8		0.1	3.2		0.2	5.6	$\mu\text{V}/\text{V}$
Supply Current Per Amplifier	$I_{SY}$	No load		600	725		600	725		600	725	$\mu\text{A}$
<b>DYNAMIC PERFORMANCE</b>												
Slew Rate	SR			0.1	0.15		0.1	0.15		0.1	0.15	$\text{V}/\mu\text{s}$
Gain Bandwidth Product	GBWP			500			500			500		kHz
Channel Separation	CS	$A_V = 1$ $V_O = 20$ V p-p $f_O = 10$ Hz <sup>2</sup>	123	135		123	135		123	135		dB
Capacitive Load Stability		$A_V = 1$ No oscillations		10			10			10		nF
<b>NOISE PERFORMANCE</b>												
Input Noise Voltage Density <sup>3</sup>	$e_n$	$f_O = 10$ Hz <sup>3</sup>		22	36		22	36		22		$\text{nV}/\sqrt{\text{Hz}}$
		$f_O = 1,000$ Hz <sup>3</sup>		11	18		11	18		11		$\text{nV}/\sqrt{\text{Hz}}$
Input Noise Current	$i_{n,p-p}$	0.1 Hz to 10 Hz		15			15			15		pA p-p
Input Noise Current Density	$i_n$	$f_O = 10$ Hz		0.6			0.6			0.6		$\text{pA}/\sqrt{\text{Hz}}$

<sup>1</sup> Guaranteed by CMR test.

<sup>2</sup> Guaranteed but not 100% tested.

<sup>3</sup> Sample tested.

# OP400

@  $V_S = \pm 15$  V,  $-55^\circ\text{C} < T_A = +125^\circ\text{C}$  for OP400A, unless otherwise noted.

**Table 2.**

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
Input Offset Voltage	$V_{OS}$		70	270		$\mu\text{V}$
Average Input Offset Voltage Drift	$TCV_{OS}$		0.3	12		$\mu\text{V}/^\circ\text{C}$
Input Offset Current	$I_{OS}$	$V_{CM} = 0$ V	01	2.5		nA
Input Bias Current	$I_B$	$V_{CM} = 0$ V	1.3	5.0		nA
Large Signal Voltage Gain	$A_{VO}$	$V_O = \pm 10$ V, $R_L = 10$ k $\Omega$ $R_L = 2$ k $\Omega$	3000 1000	9000 2300		V/mV
Input Voltage Range <sup>1</sup>	IVR		$\pm 12$	$\pm 12.5$		V
Common-Mode Rejection	CMR	$V_{CM} = \pm 12$ V	115	130		dB
OUTPUT CHARACTERISTICS						
Output Voltage Swing	$V_O$	$R_L = 10$ k $\Omega$	$\pm 12$	$\pm 12.4$		
POWER SUPPLY						
Power Supply Rejection Ratio	PSRR	$V_O = 3$ V to 18 V	0.2	3.2		$\mu\text{V/V}$
Supply Current Per Amplifier	$I_{SY}$	No load	600	775		$\mu\text{A}$
DYNAMIC PERFORMANCE						
Capacitive Load Stability		$A_V = 1$ No oscillations	8			nF

<sup>1</sup> Guaranteed by CMR test.




Figure 4. Dice Characteristics

@  $V_S = \pm 15$  V,  $-25^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$  for OP400E/F,  $0^\circ\text{C} \leq T_A \leq 70^\circ\text{C}$  for OP400G,  $-40^\circ\text{C} \leq T_A \leq +85^\circ\text{C}$  for OP400H, unless otherwise noted.

Table 3.

Parameter	Symbol	Conditions	OP400A/E			OP400F			OP400G/H			Unit
			Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
<b>INPUT CHARACTERISTICS</b>												
Input Offset Voltage	$V_{OS}$			60	220		80	350		110	400	$\mu\text{V}$
Average Input Offset Voltage Drift	$TCV_{OS}$			0.3	1.2		0.3	2.0		0.6	2.5	$\mu\text{V}/^\circ\text{C}$
Input Offset Current	$I_{OS}$	$V_{CM} = 0$ V E, F, G grades H grade		0.1	2.5		0.1	3.5		0.2	6.0	nA
Input Bias Current	$I_B$	$V_{CM} = 0$ V E, F, G grades H grade		0.1	2.5		0.1	3.5		0.2	12.0	nA
Large-Signal Voltage Gain	$A_{VO}$	$V_{CM} = 0$ V $R_L = 10$ k $\Omega$ $R_L = 2$ k $\Omega$	3000	10,000		2000	5000		2000	5000		V/mV
Input Voltage Range <sup>1</sup>	IVR		1500	2700		1000	2000		1000	2000		V/mV
Common-Mode Rejection	CMR	$V_{CM} = \pm 12$ V	$\pm 12$	$\pm 12.5$		$\pm 12$	$\pm 12.5$		$\pm 12$	$\pm 12.5$		V
<b>OUTPUT CHARACTERISTICS</b>												
Output Voltage Swing	$V_O$	$R_L = 10$ k $\Omega$ $R_L = 2$ k $\Omega$	$\pm 12$	$\pm 12.4$		$\pm 12$	$\pm 12.4$		$\pm 12$	$\pm 12.6$		V
			$\pm 11$	$\pm 12$		$\pm 11$	$\pm 12$		$\pm 11$	$\pm 12.2$		V
<b>POWER SUPPLY</b>												
Power Supply Rejection Ratio	PSRR	$V_S = \pm 3$ V to $\pm 18$ V		0.15	3.2		0.15	5.6		0.3	10.0	$\mu\text{V/V}$
Supply Current Per Amplifier	$I_{SY}$	No load		600	775		600	775		600	775	$\mu\text{A}$
<b>DYNAMIC PERFORMANCE</b>												
Capacitive Load Stability		No oscillations		10			10			10		nF

<sup>1</sup> Guaranteed by CMR test.

## ABSOLUTE MAXIMUM RATINGS

Table 4.

Parameter	Rating
Supply Voltage	$\pm 20$ V
Differential Input Voltage	$\pm 30$ V
Input Voltage	Supply voltage
Output Short-Circuit Duration	Continuous
Storage Temperature Range P, Y Packages	-65°C to +150°C
Lead Temperature (Soldering 60 sec)	300°C
Junction Temperature ( $T_j$ )	-65°C to +150°C
Operating Temperature Range OP400A	-55°C to +125°C
OP400E, OP400F	-25°C to +85°C
OP400G	0°C to 70°C
OP400H	-40°C to +85°C

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Absolute maximum ratings apply to both dice and packaged parts, unless otherwise noted.

### THERMAL RESISTANCE

$\theta_{JA}$  is specified for worst-case mounting conditions, that is,  $\theta_{JA}$  is specified for device in socket for CERDIP and PDIP packages;  $\theta_{JA}$  is specified for device soldered to printed circuit board for SOIC package.

Table 5. Thermal Resistance

Package Type	$\theta_{JA}$	$\theta_{JC}$	Unit
14-pin ceramic DIP (Y)	94	10	°C/W
14-pin plastic DIP (P)	76	33	°C/W
16-pin SOIC (S)	88	23	°C/W

### ESD CAUTION

ESD (electrostatic discharge) sensitive device. Electrostatic charges as high as 4000 V readily accumulate on the human body and test equipment and can discharge without detection. Although this product features proprietary ESD protection circuitry, permanent damage may occur on devices subjected to high energy electrostatic discharges. Therefore, proper ESD precautions are recommended to avoid performance degradation or loss of functionality.



## TYPICAL PERFORMANCE CHARACTERISTICS




Figure 5. Warm-Up Drift




Figure 8. Input Offset Current vs. Temperature




Figure 6. Input Offset Voltage vs. Temperature




Figure 9. Input Bias Current vs. Common-Mode Voltage




Figure 7. Input Bias Current vs. Temperature




Figure 10. Common-Mode Rejection vs. Frequency

# OP400




Figure 11. Noise Voltage Density vs. Frequency




Figure 12. Current Noise Density vs. Frequency




Figure 13. 0.1 Hz to 10 Hz Noise




Figure 14. Total Supply Current vs. Supply Voltage




Figure 15. Total Supply Current vs. Temperature














Figure 16. Power Supply Rejection vs. Frequency





# OP400



00304-025



00304-026



00304-027




Figure 29. Noise Test Schematic




Figure 30. Burn-In Circuit

## APPLICATIONS

The OP400 is inherently stable at all gains and is capable of driving large capacitive loads without oscillating. Nonetheless, good supply decoupling is highly recommended. Proper supply decoupling reduces problems caused by supply line noise and improves the capacitive load driving capability of the OP400.

Total supply current can be reduced by connecting the inputs of an unused amplifier to  $-V$ . This turns the amplifier off, lowering the total supply current.

### DUAL LOW POWER INSTRUMENTATION AMPLIFIER

A dual instrumentation amplifier that consumes less than 33 mW of power per channel is shown in Figure 31. The linearity of the instrumentation amplifier exceeds 16 bits in gains of 5 to 200 and is better than 14 bits in gains from 200 to 1000. CMRR is above 115 dB ( $G = 1000$ ). Offset voltage drift is typically  $0.4 \mu\text{V}/^\circ\text{C}$  over the military temperature range, which is comparable to the best monolithic instrumentation amplifiers. The bandwidth of the low power instrumentation amplifier is a function of gain and is shown in Table 6.

The output signal is specified with respect to the reference input, which is normally connected to analog ground. The reference input can be used to offset the output from  $-10 \text{ V}$  to  $+10 \text{ V}$  if required.

**Table 6. Gain Bandwidth**

Gain	Bandwidth
5	150 kHz
10	67 kHz
100	7.5 kHz
1000	500 Hz




Figure 31. Dual Low Power Instrumentation Amplifier

0304-030

## BIPOLAR CURRENT TRANSMITTER

In the circuit of Figure 32, which is an extension of the standard three op amp instrumentation amplifier, the output current is proportional to the differential input voltage. Maximum output current is  $\pm 5$  mA with voltage compliance equal to  $\pm 10$  V when using  $\pm 15$  V supplies. Output impedance of the current transmitter exceeds  $3\text{ M}\Omega$  and linearity is better than 16 bits with gain set for a full-scale input of  $\pm 100\text{ }\mu\text{V}$ .

## DIFFERENTIAL OUTPUT INSTRUMENTATION AMPLIFIER

The output voltage swing of a single-ended instrumentation amplifier is limited by the supplies, normally at  $\pm 15$  V, to a maximum of 24 V p-p. The differential output instrumentation amplifier of Figure 33 can provide an output voltage swing of 48 V p-p when operated with  $\pm 15$  V supplies. The extended output swing is due to the opposite polarity of the outputs. Both outputs swing 24 V p-p but with opposite polarity, for a total output voltage swing of 48 V p-p. The reference input can be used to set a common-mode output voltage over the range  $\pm 10$  V. The PSRR of the amplifier is less than  $1\text{ }\mu\text{V/V}$  with CMRR ( $G = 1000$ ) better than 115 dB. Offset voltage drift is typically  $0.4\text{ }\mu\text{V}/^\circ\text{C}$  over the military temperature range.




Figure 32. Bipolar Current Transmitter





Figure 33. Differential Output Instrumentation Amplifier


# MULTIPLE OUTPUT TRACKING VOLTAGE REFERENCE

Figure 34 shows a circuit that provides outputs of 10 V, 7.5 V, 5 V, and 2.5 V for use as a system voltage reference. Maximum output current from each reference is 5 mA with load regulation under  $25 \mu\text{V}/\text{mA}$ . Line regulation is better than  $15 \mu\text{V}/\text{V}$  and output voltage drift is under  $20 \mu\text{V}/^\circ\text{C}$ . Output voltage noise from 0.1 Hz to 10 Hz is typically  $75 \mu\text{V p-p}$  from the 10 V output and proportionately less from the 7.5 V, 5 V, and 2.5 V outputs.



*Figure 34. Multiple Output Tracking Voltage Reference*


## OUTLINE DIMENSIONS




CONTROLLING DIMENSIONS ARE IN INCHES; MILLIMETER DIMENSIONS (IN PARENTHESES) ARE ROUNDED-OFF INCH EQUIVALENTS FOR REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

Figure 35. 14-Lead Ceramic Dual In-Line Package [CERDIP]  
(Q-14)  
[Y-Suffix]

Dimensions shown in inches and (millimeters)



COMPLIANT TO JEDEC STANDARDS MS-013-AA  
CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS (IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.



CONTROLLING DIMENSIONS ARE IN INCHES; MILLIMETER DIMENSIONS (IN PARENTHESES) ARE ROUNDED-OFF INCH EQUIVALENTS FOR REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

Figure 36. 14-Lead Plastic Dual In-Line Package [PDIP]  
(N-14)  
[P-Suffix]

Dimensions shown in inches and (millimeters)

# OP400

## ORDERING GUIDE

Model	Temperature Range	Package Description	Package Option
OP400AY	-55°C to +125°C	14-Lead CERDIP	Y-Suffix (Q-14)
OP400EY	-25°C to +85°C	14-Lead CERDIP	Y-Suffix (Q-14)
OP400FY	-25°C to +85°C	14-Lead CERDIP	Y-Suffix (Q-14)
OP400GP	0°C to +70°C	14-Lead PDIP	P-Suffix (N-14)
OP400GPZ <sup>1</sup>	0°C to +70°C	14-Lead PDIP	P-Suffix (N-14)
OP400HP	-40°C to +85°C	14-Lead PDIP	P-Suffix (N-14)
OP400HPZ <sup>1</sup>	-40°C to +85°C	14-Lead PDIP	P-Suffix (N-14)
OP400GS	0°C to +70°C	16-Lead SOIC	S-Suffix (R-16)
OP400GS-REEL	0°C to +70°C	16-Lead SOIC	S-Suffix (R-16)
OP400GSZ <sup>1</sup>	0°C to +70°C	16-Lead SOIC	S-Suffix (R-16)
OP400GSZ-REEL <sup>1</sup>	0°C to +70°C	16-Lead SOIC	S-Suffix (R-16)
OP400HS	-40°C to +85°C	16-Lead SOIC	S-Suffix (R-16)
OP400HS-REEL	-40°C to +85°C	16-Lead SOIC	S-Suffix (R-16)
OP400HSZ <sup>1</sup>	-40°C to +85°C	16-Lead SOIC	S-Suffix (R-16)
OP400HSZ-REEL <sup>1</sup>	-40°C to +85°C	16-Lead SOIC	S-Suffix (R-16)
OP400GBC		Die	

<sup>1</sup> Z = Pb-free part.

## SMD PARTS AND EQUIVALENTS

SMD Part Number <sup>1</sup>	ADI Equivalent
5962-8777101M3A	OP400ATCMDA
5962-8777101MCA	OP400AYMDA

<sup>1</sup> For military processed devices, please refer to the standard microcircuit drawing (SMD) available at [www.dscc.dla.mil/programs/milspec/default.asp](http://www.dscc.dla.mil/programs/milspec/default.asp).