



Approval	 	
<b>Capability</b>		
Standard	<b>UL</b>	<b>IEC</b>
Rated Voltage	600V	800V
Rated Current	20A	24A
Wire size	24-12AWG	0.2-2.5mm <sup>2</sup>
T/W/End plate	5.2/42.5/1.6mm	
Height(mm)(NS35:7.5/NS35:15/NS32)	42/54.5/52mm	
Rated surge voltage/Contamination Class	8KV/3	
Stripping length	7mm	
Screw thread/Tightening torque	M3/0.5N.m/4.5Lb-in	
Internal cylindrical gage	A3	
Insulating Material/Inflammability class	PA/V-0	
<b>Specification</b>	<b>Model</b>	<b>Pieces</b>
(1) Terminal block	PC 2.5	50
(2) End cover	D-PC 2.5	200
(3) Fixed bridge	FBRI 2-5	100
2-P	FBRI 3-5	10
3-P	FBRI 5-5	10
5-P	FBRI 10-5	10
10-P		
(4) Step bracket		
(5) Insertion bridge	EB 2-5	150
2-P	EB 3-5	150
3-P	EB 10-5	50
10-P		
(6) Isolator bridge bar, 10P		
(7) Bridge bar isolator		
(8) Switching bridge		
(9) Separating plate	TS-K	1000
(10) Separating plate, width 1.5mm	ATP-PC	50
(11) Test plug socket	DSB 3/10/4	100
(12) Test plug socket, insulated	DSBJ 3/13/4	100
(13) Zack strip	ZB5	300

### HOW TO ORDER :

-  P - 1  - 

X	X	X
Customer Request		

Series No.

No. of pole

Color

1	Gray	4	Green	7	Trans-parent
2	Blue	5	Orange	8	Yellow
3	Black	6	Red	9	White

 mm (INCH)	 <b>DEGSON ELECTRONICS CO., LTD.</b>
 THROATLE PROJECTION	<b>NAME</b> <b>PC 2.5</b>